

Precision Industrial Components

Precise Plain Washer

Specifications:

IMPERIAL WASHER DIMENSIONS											
FOR THREAD SIZE		BS 3410 TABLE 3	FOR UNC, BSW & BSF	BS 3410 TABLE 4 (ID AS FOR TABLE 3)							
	ID	OD	LIGHT THICKNESS	HEAVY THICKNESS	OD	LIGHT THICKNESS	HEAVY THICKNESS				
1/4	0.265-0.27	0.557-0.562	20 SWG / 0.036	17 SWG / 0.056	0.62 - 0.625	19 SWG / 0.040	20 SWG / 0.036				
5/16	0.328-0.333	0.62-0.625	19 SWG / 0.040	15 SWG / 0.072	0.745-0.75	18 SWG / 0.048	19 SWG / 0.212				
3/8	0.39-0.395	0.745-0.75	18 SWG / 0.048	15 SWG / 0.072	0.87-0.875	18 SWG / 0.048	18 SWG / 0.212				
7/16	0.453-0.458	0.87-0.875	18 SWG / 0.048	13 SWG - 0.092	0.995-1	17 SWG / 0.056	18 SWG / 0.212				
1/2	0.515-0.52	0.995-1	17 SWG / 0.056	13 SWG / 0.092	1.115-1.125	17 SWG / 0.056	17 SWG / 0.212				
9/16	0.588-0.593	1.115-1.125	17 SWG / 0.056	12 SWG / 0.104	1.240-1.250	17 SWG / 0.056	17 SWG / 0.212				
5/8	0.651-0.656	1.240-1.2 <mark>50</mark>	15 SWG / 0.072	11 SWG / 0,116	1.365-1.375	15 SWG / 0.072	15 SWG / 0.212				
3/4	0.776-0.781	1.49-1.5	15 SWG / 0.072	10 SWG / 0.128	1.615 - 1.625	15 SWG / 0.072	10 SWG / 0.128				
7/8	0.901-0.906	1.615-1.625	15 SWG / 0.072	9 SWG / 0.144	1.865-1.875	15 SWG / 0.072	9 SWG / 0.144				
1	1.026-1.031	1.865-1.875	15 SWG / 0.072	8 SWG / 0.160	2.115-2.125	13 SWG / 0.092	8 SWG / 0.160				
1.1/8	1.151-1.156	2.115-2.125	13 SWG / 0.092	7 SWG / 0.176	2.355-2.375	12 SWG / 0.104	7 SWG / 0.176				
1.1/4	1.276-1.281	2.355-2.375	11 SWG / 0.116	7 SWG / 0.176	2.605-2.625	11 SWG / 0.116	7 SWG / 0.176				
1.3/8	1.401-1.406	2.605-2.625	G	6 SWG / 0.192	2.855-2.875	10 SWG / 0.128	6 SWG / 0.192				
1.1/2	1.526-1.531	2.855-2.875	ä	6 SWG / 0.192	3.095-3.125	10 SWG / 0.128	6 SWG / 0.192				
1.3/4	1.776-1.785	3.345-3.375	ä	5 SWG / 0.212	3.595-3.625	10 SWG / 0.128	5 SWG / 0.212				
2	2.062-2.031	3.595-3.625	-	5 SWG / 0.212	4.095-4.125	10 SWG / 0.128	5 SWG / 0.212				

IMPERIAL WASHER DIMENSIONS										
FOR THREAD CITE	В	S 3410 TABLE 1 FOR SMALL BA S	BS 3410 TABLE 2 LARGE (ID AS FOR TABLE 3)							
FOR THREAD SIZE	ID	OD OD	THICKNESS	OD	LIGHT THICKNESS					
2BA	0.197-0.202	0.386-0.391	21 SWG 0.032	0.495-0.500	18 SWG 0.048					
4BA	0.152-0.157	0.296-0.301	22 SWG 0.028	0.373-0.378	19 SWG 0.040					
6BA	0.118-0.123	0.228-0.233	23 SWG 0.024	0.283-0.288	20 SWG 0.036					
8BA	0.094-0.099	0.180-0.185	25 SWG 0.020	0.223-0.228	25 SWG 0.020					



M/S. Precision Industrial Components

5, Puhram Estate, Gondal Road, B/h. Shivalik - 5, Rajkot - 360002 . Gujarat (India).

Contact Details:

Email: precisepin@yahoo.co.in, parekh.nishit@live.com, precisecotterpin@gmail.com Phone (Office): (0281) 2363560.

Cell Phone: (+91) 93741 00327 (Mr. Dakshesh Parekh) (+91) 81550 50327 (Mr. Nishit Parekh)